

ANPx321

Technical Specifications

Technology	
travel mechanism	inertial piezo drive
positioner type	linear
Size and Dimensions	
footprint; height	41.6x40; 11.5mm
max installation space	40x56.6; 11.5mm
weight	74 g
Materials	
positioner body	titanium
actuator	PZT ceramics
connecting wires	insulated twisted pair, copper
bearings	ceramics
Options	
environmental options	/HV, /LT, /LT/HV, /LT/UHV, /RT, /UHV
Compatibility with Electronics	
ANC300 piezo positioning controller	ANM150, ANM300
Load (@ ambient conditions)	
maximum torque on the axis	10 Ncm
maximum load	20 N
maximum dynamic force along the axis	2 N
Coarse Positioning Mode	
input voltage range	0 - 60 V
typical actuator capacitance @ 300 K	1.6 µF
typical actuator capacitance @ 4 K	0.22 µF
travel range (step mode)	15 mm
typical minimum step size @ 300 K	100 nm
typical minimum step size @ 4 K	20 nm
maximum drive velocity @ 300 K	approx. 3 mm/s
Fine Positioning Mode	
fine positioning range @ 300 K	7.5 µm
fine positioning range @ 4 K	1.2 µm
fine positioning resolution	sub-nm
input DC voltage range @ 300 K	0 - 100 V
input DC voltage range @ 4 K	0 - 150 V
Accuracy of Movement	
repeatability of step sizes	typically 5 % over full range
forward / backward step asymmetry	typically 5 %

Mounting	
no. of through holes at the top	4
diameter of through holes at the top	2.2 mm
type of screw at the top	M2
no. of threads at the bottom	4
type of screw at the bottom	M2.5 x 2 mm
no. of threads for load on top	10
type of screw for load on top	M2 x 3 mm
Working Conditions	
mounting orientation	axis horizontal
magnetic field range	0 - 31 T
minimum pressure (/RT)	1E-4 mbar
minimum pressure (/HV)	1E-8 mbar
minimum pressure (/UHV)	5E-11 mbar
temperature range (/RT)	273K .. 373K
temperature range (/LT)	10mK .. 373K
Connectors and Feedthroughs	
cable	30 cm cable with connector
electrical feedthrough solution	VFT/LT
Versions	
/RT version	1006724
/HV version	1006725
/UHV version	1006726
/LT version	1007258
/LT/HV version	1007259
/LT/UHV version	1007260
/HL/RT version	1008325
/HL/HV version	1008326
/HL/UHV version	1008327
/HL/LT version	1008328
/HL/LT/HV version	1008329
/HL/LT/UHV version	1008330

Technical Drawings

