

ANPx51

Technical Specifications

Technology	
travel mechanism	inertial piezo drive
positioner type	linear
Size and Dimensions	
footprint; height	15x15; 9.2mm
max installation space	15x18; 9.2mm
weight	7 g
Materials	
positioner body	titanium (upgrade option: copper beryllium)
actuator	PZT ceramics
connecting wires	insulated twisted pair, copper
Options	
environmental options	/HV, /LT, /LT/HV, /LT/UHV, /RT, /UHV
Compatibility with Electronics	
ANC300 piezo positioning controller	ANM150, ANM300
Load (@ ambient conditions)	
maximum torque on the axis	10 Ncm
maximum load	0.25 N
maximum dynamic force along the axis	1 N
Coarse Positioning Mode	
input voltage range	0 - 60 V
typical actuator capacitance @ 300 K	1.11 µF
typical actuator capacitance @ 4 K	0.15 µF
travel range (step mode)	3 mm
typical minimum step size @ 300 K	50 nm
typical minimum step size @ 4 K	10 nm
maximum drive velocity @ 300 K	approx. 1 mm/s
Fine Positioning Mode	
fine positioning range @ 300 K	5 µm
fine positioning range @ 4 K	0.8 µm
fine positioning resolution	sub-nm
input DC voltage range @ 300 K	0 - 100 V
input DC voltage range @ 4 K	0 - 150 V
Accuracy of Movement	
repeatability of step sizes	typically 5 % over full range
forward / backward step asymmetry	typically 5 %

Mounting	
no. of through holes at the top	2
diameter of through holes at the top	1.7 mm
type of screw at the top	M1.6
no. of threads at the bottom	2
type of screw at the bottom	M2 x 2.5 mm
no. of threads for load on top	4
type of screw for load on top	M1.6 x 2.5 mm
Working Conditions	
mounting orientation	axis horizontal
magnetic field range	0 - 31 T
minimum pressure (/RT)	1E-4 mbar
minimum pressure (/HV)	1E-8 mbar
minimum pressure (/UHV)	5E-11 mbar
temperature range (/RT)	273K .. 373K
temperature range (/LT)	10mK .. 373K
Connectors and Feedthroughs	
connector type	2-pole pin plug, ø 0.5 mm, d = 2 mm
cable	30 cm cable with connector
electrical feedthrough solution	VFT/LT
Versions	
/RT version	1002223
/HV version	1002219
/UHV version	1002224
/LT version	1007705
/LT/HV version	1002221
/LT/UHV version	1002222

Technical Drawings

